

Specification Sheet

Part Number: RT50SSF

 Product Image

Arrowhead is easy to install without the need for use with a tool.

Arrowhead gives a firm and secure fixing and can be used in multiple panel thicknesses.

Design provides low insertion and high extraction force ideal for the production environment.

1-Piece Cable Tie/Arrowhead Mount w Wings, Releasable, 5.0"L, 1.0" Bundle Dia, PA66, Natural, 100/pkg

Article Number 115-00077

Type RT50SSF

Color Natural (NA)

Quantity Per bag

Product Description Arrowhead Ties ensure a firm and secure fixing. The legs take up any variation in panel thickness enabling one part to suit many applications. These are quick and easy to install, and can be used with various surfaces such as sheet metal, wood, and cast iron.

Short Description 1-Piece Cable Tie/Arrowhead Mount w Wings, Releasable, 5.0"L, 1.0" Bundle Dia, PA66, Natural, 100/pkg

Global Part Name RT50SSF-PA66-NA

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	5.12
Length L (Metric)	130.0
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	Yes
Width W (Imperial)	0.19
Width W (Metric)	4.8
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.02
Bundle Diameter Max (Metric)	26.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.3
Height H (Imperial)	0.36

Height H (Metric)	9.2
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.10
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	2.6
Mounting Hole Diameter D (Imperial)	0.24 - 0.3
Mounting Hole Diameter D (Metric)	6.0 - 7.5 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.3
Mounting Hole Diameter D Max (Metric)	7.5

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL 94 V-2

Halogen Free Yes

Use Conditions For Indoor Use Only

Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	UL ANSI/UL 62275 UL ANSI/UL 1565
UL Recognized (US)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)