

## Specification Sheet

Part Number: DCT110HIRK2



Provides dual separation between bundles to prevent chafing and abrasion.

150lb. tensile strength ensures enough strength for heavy duty applications.

Straps are releasable for increased serviceability.

Dual Clamp Tie, 19.20" Long, 0.25" Stud Dia, 2.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black, 50/pkg

Article Number 115-31100

Type DCT11

Color Black (BK)

Quantity Per bag

Product Description Dual-Clamp Ties are designed to provide parallel separation between hoses, wires, cables, and tubing to protect them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of trucks, trailers, and heavy duty equipment. The unique one-piece design features the dual head centered on the strap.

Short Description Dual Clamp Tie, 19.20" Long, 0.25" Stud Dia, 2.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black, 50/pkg

Global Part Name DCT11-PA66HIRHSUV-BK

|                                     |                  |
|-------------------------------------|------------------|
| Minimum Tensile Strength (Imperial) | 150              |
| Minimum Tensile Strength (Metric)   | 667              |
| Length L (Imperial)                 | 19.2             |
| Length L (Metric)                   | 487.68           |
| Fixation Method                     | Weld Stud Fixing |
| Identification Plate Position       | none             |
| Releasable Closure                  | No               |
| Tie Closure                         | plastic pawl     |
| Variant                             | Inside Serrated  |
| Width W (Imperial)                  | 0.5              |
| Width W (Metric)                    | 12.7             |
| Bundle Diameter Min (Imperial)      | 0.25             |
| Bundle Diameter Min (Metric)        | 6.4              |
| Bundle Diameter Max (Imperial)      | 2.28             |
| Bundle Diameter Max (Metric)        | 58.0             |
| Thickness T (Imperial)              | 0.06             |

|   |  |
|---|--|
| Thickness T (Metric)                    | 1.4  |
| Height H (Imperial)                     | 0.8  |
| Height H (Metric)                       | 20.32  |
| Mounting Hole Diameter D (Imperial)     | 0.20   |
| Mounting Hole Diameter D (Metric)       | 6.2 mm   |
| Mounting Hole Diameter D Min (Imperial) | 0.20   |
| Mounting Hole Diameter D Max (Imperial) | 0.20   |
| Mounting Hole Diameter D Max (Metric)   | 6.2  |
| Stud Diameter (Metric)                  | M6   |
| Stud Diameter (Imperial)                | 1/4  |
| Material                                | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut                       | PA66HIRHSUV  |
| Flammability                            | UL 94 HB   |
| UV Resistant (Yes/No)                   | Yes  |
| Use Conditions                          | For Indoor and Outdoor Use   |

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 50

Customs Number 3926909988