HellermannTyton

Specification Sheet

Part Number: 132-00034



Unique two piece tie allows parallel entry and exit through the head for easy assembly.

High impact, heat stabilized material gives strength needed for trucking and heavy equipment applications.

Button Head Cable Tie with Retainers and Pilot Bushings, 15.0" Long, PA66HIRHSUV/PA66HS, Black, 2000/pkg

Article Number 132-00034

Type BT130LDP

Color Black (BK)

Quantity Per carton

Product Description The button head tie is a two piece tie providing for parallel entry and

exit through the head. The strap contains serrations on both sides, and has two opposed pawls recessed within a domed head. This design allows the strap to be directed clockwise or counter-clockwise prior to

insertion into the head, enabling bi-directional looping.

Short Description Button Head Cable Tie with Retainers and Pilot Bushings, 15.0" Long,

PA66HIRHSUV/PA66HS, Black, 2000/pkg

Global Part Name BT130LDP-PA66HIRHSUV/PA66HS-BK

Minimum Tensile Strength (Imperial)	130
Minimum Tensile Strength (Metric)	578
Length L (Imperial)	15.0
Length L (Metric)	381.5
Fixation Method	Button Head
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.3
Width W (Metric)	7.6
Bundle Diameter Min (Imperial)	0.25
Bundle Diameter Min (Metric)	6.4
Bundle Diameter Max (Imperial)	4.33
Bundle Diameter Max (Metric)	110.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized

(PA66HIRHSUV) Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS PA66HIRHSUV

Material Cable Tie Polyamide 6.6 high impact modified, heat and UV stabilized

(PA66HIRHSUV)

Material Head Polyamide 6.6 heat stabilized (PA66HS)

Flammability UL 94 HB

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33)

Yes

Package Quantity (Imperial) 2000

Package Quantity (Metric) 2000

Customs Number 3926909988