

Specification Sheet

Part Number: 133-02029



Easy assembly without the need of a tool.

Disc covers mounting hole and minimizes ingress of dust, dirt and water.

Standard geometry for example fir tree or arrowhead.

Push Pin, Mounting Hole Dia. 6.5x12.5mm, PA66HIRHS, Black, 3000/carton

Article Number	133-02029
Type	PLUGFTOVALXL
Color	Black (BK)
Quantity Per	carton
Product Description	Developed especially for the automotive industry in applications including trunks, doors, wheel housings and dash panels.
Short Description	Push Pin, Mounting Hole Dia. 6.5x12.5mm, PA66HIRHS, Black, 3000/carton
Global Part Name	PLUGFTOVALXL-PA66HIRHSUV-BK

Length L (Imperial)	0.77
Length L (Metric)	19.6
Fixation Method	Blind Plug
Width W (Imperial)	0.54
Width W (Metric)	13.62
Height H (Imperial)	0.78
Height H (Metric)	19.7
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.31
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	8.0
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " 0.25 x 0.50 " 0.25 x 0.50 " 0.27 x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 7.0 x 12.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	13.0

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988