

Specification Sheet

Part Number: 133-02798



Clip can be installed by hand – no need for hardware or tools.

Design provides low insertion and high extraction force, for simple, secure performance.

Clip keeps bundle away from areas that could cause damage due to rubbing.

Standoff Bundling Clip, 40.0 mm Long, 6.2 - 6.5 mm Mounting Hole Dia., PP, Gray, 2400/carton

Article Number	133-02798
----------------	-----------

Type	SOC40OS99.5FT6.5
------	------------------

Color	Gray (GY)
-------	-----------

Quantity Per	carton
--------------	--------

Product Description	Standoff bundling clips provide a straightforward way to secure cable bundles, hoses or pipes. The bundle fastens to the tape bar using tape or cable ties. Multiple orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standoff keeps bundles away from mounting area to prevent them from damage due to rubbing.
---------------------	---

Short Description	Standoff Bundling Clip, 40.0 mm Long, 6.2 - 6.5 mm Mounting Hole Dia., PP, Gray, 2400/carton
-------------------	--

Global Part Name	SOC40OS99.5FT6.5-PP-GY
------------------	------------------------

Length L (Imperial)	1.57
---------------------	------

Length L (Metric)	40.0
-------------------	------

Fixation Method	Fir tree for round holes
-----------------	--------------------------

Width W (Imperial)	0.37
--------------------	------

Width W (Metric)	9.5
------------------	-----

Height H (Imperial)	0.71
---------------------	------

Height H (Metric)	18.0
-------------------	------

Panel Thickness Min (Imperial)	0.02
--------------------------------	------

Panel Thickness Max (Imperial)	0.16
--------------------------------	------

Panel Thickness Min (Metric)	0.5
------------------------------	-----

Panel Thickness Max (Metric)	4.0
------------------------------	-----

Mounting Hole Diameter D (Imperial)	0.24 - 0.26
-------------------------------------	-------------

Mounting Hole Diameter D (Metric)	6.2 - 6.5 mm
-----------------------------------	--------------

Mounting Hole Diameter D Min (Imperial)	0.24
---	------

Mounting Hole Diameter D Max (Imperial)	0.26
---	------

Mounting Hole Diameter D Max (Metric) 6.5

Material Polypropylene (PP)

Material Shortcut PP

Flammability UL 94 HB

Use Conditions For Indoor Use Only

Operating Temperature -40°F to +239°F (-40°C to +115°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 2400

Package Quantity (Metric) 2400

Customs Number 3926909988