

Specification Sheet

Part Number: 133-02835



Arrowhead design makes installation by hand quick and easy without the need for tools.

Ties "click" into place, providing audible confirmation insertion is complete.

Design provides low insertion and high extraction force.

1-Piece Cable Tie/Arrowhead Mount, 5.8"L, 50lb, Hole Dia 0.24 - 0.28", PA66HIRHS, Gray, 2400/ctn

Article Number 133-02835

Type T50SOSAH6.5

Color Gray (GY)

Quantity Per carton

Product Description One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. Wing design helps stabilize the tie in high vibration applications. Mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description 1-Piece Cable Tie/Arrowhead Mount, 5.8"L, 50lb, Hole Dia 0.24 - 0.28", PA66HIRHS, Gray, 2400/ctn

Global Part Name T50SOSAH6.5-PA66HIRHS-GY

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 5.83

Length L (Metric) 148.1

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.19

Width W (Metric) 4.8

Bundle Diameter Min (Imperial) 0.04

Bundle Diameter Min (Metric) 1.0

Bundle Diameter Max (Imperial) 1.38

Bundle Diameter Max (Metric) 35.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Height H (Imperial)	0.039
Height H (Metric)	19.0
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.06
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	1.5
Mounting Hole Diameter D (Imperial)	0.24 - 0.26; 0.24 - 0.28
Mounting Hole Diameter D (Metric)	6.2 - 6.5 mm 6.0 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter (Metric)	19.0
Disc Diameter (Imperial)	0.039

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	2400
Package Quantity (Metric)	2400
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)