

Specification Sheet

Part Number: 133-03395



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance

Conduit Clamps, Size 6, Mounting Hole 8.8 mm, Threaded, PP, Black, 800/pkg

Article Number 133-03395

Type CDC6B90AOS8AM8

Color Black (BK)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters.

Short Description Conduit Clamps, Size 6, Mounting Hole 8.8 mm, Threaded, PP, Black, 800/pkg

Global Part Name CDC6B90AOS8AM8-PP-BK

Length L (Imperial) 2.17

Length L (Metric) 55.1

Offset Length (Imperial) 0.54

Offset Length (Metric) 13.7

Fixation Method screwable

Width W (Imperial) 2.3

Width W (Metric) 59.2

Bundle Diameter Max (Imperial) 0.24

Bundle Diameter Max (Metric) 6.0

Height H (Imperial) 2.62

Height H (Metric) 66.5

Diameter D (Imperial) 0.31

Diameter D (Metric) 8.0

Mounting Hole Diameter D (Imperial) 0.35

Mounting Hole Diameter D (Metric) 8.8 mm

Stud Diameter (Metric)	M8
Stud Diameter (Imperial)	M8
Material	Polypropylene (PP)
Material Shortcut	PP
Flammability	UL 94 HB
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +239°F (-40°C to +115°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	800
Package Quantity (Metric)	800
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)