

Specification Sheet

Part Number: 133-03429



- Can be easily assembled to convoluted tubing and reliably remain in position
- Internal rib prevents movement or rattling
- Multiple configurations to mount to a variety of surfaces
- Releaseable to allow for maintenance

Conduit Clamps, Size 22, Mounting Hole 6.5 mm, Offset 20.2 mm, PA66, Black, 600/carton

Article Number	133-03429
Type	CDC22OSL22.15M6
Color	Black (BK)
Quantity Per	carton
Product Description	The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters.
Short Description	Conduit Clamps, Size 22, Mounting Hole 6.5 mm, Offset 20.2 mm, PA66, Black, 600/carton

Global Part Name	CDC22OSL22.15M6-PA66-BK
------------------	-------------------------

Length L (Imperial)	2.59
---------------------	------

Length L (Metric)	65.8
-------------------	------

Offset Length (Imperial)	0.8
--------------------------	-----

Offset Length (Metric)	20.2
------------------------	------

Fixation Method	screwable
-----------------	-----------

Width W (Imperial)	1.8
--------------------	-----

Width W (Metric)	45.0
------------------	------

Bundle Diameter Max (Imperial)	0.87
--------------------------------	------

Bundle Diameter Max (Metric)	22.0
------------------------------	------

Height H (Imperial)	2.87
---------------------	------

Height H (Metric)	72.8
-------------------	------

Diameter D (Imperial)	0.93
-----------------------	------

Diameter D (Metric)	23.7
---------------------	------

Mounting Hole Diameter D (Imperial)	0.26
-------------------------------------	------

Mounting Hole Diameter D (Metric)	6.5 mm
-----------------------------------	--------

Stud Diameter (Metric)	M6
Stud Diameter (Imperial)	M6
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	600
Package Quantity (Metric)	600
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)