

## Specification Sheet

Part Number: 133-03474

Clamp includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.

Fir tree design provides low insertion force and high extraction force.

Extended fir tree allows for a wide range of panel thicknesses.



Convoluted Tubing Clamp, Size 25, 6.5 mm Hole Dia., 40.5 mm Offset, PA66, Black, 500/carton

Article Number 133-03474

Type CDC25S40M6

Color Black (BK)

Quantity Per carton

Product Description Convoluted Tubing Clamps provide a quick and easy method for firmly securing corrugated tubing to a surface. This application is popular in a variety of industries such as the wire harness, automotive, trucking and heavy equipment manufacturing industries.

Short Description Convoluted Tubing Clamp, Size 25, 6.5 mm Hole Dia., 40.5 mm Offset, PA66, Black, 500/carton

Global Part Name CDC25S40M6-PA66HS-BK

Length L (Imperial)	2.94
Length L (Metric)	74.8
Offset Length (Imperial)	1.59
Offset Length (Metric)	40.5
Fixation Method	screwable
Width W (Imperial)	0.9
Width W (Metric)	23.0
Bundle Diameter Max (Imperial)	0.98
Bundle Diameter Max (Metric)	25.0
Height H (Imperial)	3.13
Height H (Metric)	79.6
Diameter D (Imperial)	1.06
Diameter D (Metric)	27.0
Mounting Hole Diameter D (Imperial)	0.25 - 0.26
Mounting Hole Diameter D (Metric)	6.4 - 6.6 mm
Mounting Hole Diameter D Min (Imperial)	0.25

Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.6
Stud Diameter (Metric)	M6
Stud Diameter (Imperial)	M6
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V-2
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500

Customs Number

3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)