

Specification Sheet

Part Number: 133-04044

Secures two routings together while keeping them separated, to prevent chafing or heat transfer

Inverted retaining legs and narrow opening prevent inadvertent disengagement

Controlled flex and angled entry promote easy installation

Robust arrowhead design provides low insertion effort yet delivers exceptional retention strength in a 65 mm hole

For use with routings of the following size: 2x 47-51mm



Tube and Pipe Clip with 6.5mm Arrowhead, 1.2-1.6mm Panel Thickness, PA66HIRHS, Black, 5000/ctn

Article Number 133-04044

Type PC5X2SO

Color Black (BK)

Quantity Per carton

Product Description This clip features a modular design that can be used individually or lined together to secure multiple pipes or hoses.

Short Description Tube and Pipe Clip with 6.5mm Arrowhead, 1.2-1.6mm Panel Thickness, PA66HIRHS, Black, 5000/ctn

Global Part Name PC5X2SO-PA66HIRHS-BK

Length L (Imperial)	0.97
Length L (Metric)	23.74
Fixation Method	Arrowhead
Width W (Imperial)	0.88
Width W (Metric)	22.35
Height H (Imperial)	1.14
Height H (Metric)	28.9
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.04
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	1.0
Mounting Hole Diameter D (Imperial)	0.24" x 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27

Mounting Hole Diameter D Max (Metric) 6.9

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

UV Resistant (Yes/No) No

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +230°F (-40°C to +110°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 5008

Package Quantity (Metric) 5000

Customs Number 3926909988