

Specification Sheet

Part Number: 133-04379



Arrowhead design makes installation by hand quick and easy.

Ties click into place upon final installation, signaling to installer insertion is complete. Design provides low insertion and high extraction force.

1-Pc. Cable Tie/Arrowhead Mount with Seal, 7.3" Long, 50lb Tensile Strength, PA66/PA66HS, Black, 800/carton

Article Number	133-04379
Type	T50R0AH712PT1.5MD
Color	Black (BK)
Quantity Per	carton
Product Description	Arrowhead push ties with rubber seal secure fast and are easy to apply. The special rubber seal minimizes water and debris from passing through the mounting hole. The anchor adjusts for variations in panel thicknesses, ensuring secure attachment at all times.
Short Description	1-Pc. Cable Tie/Arrowhead Mount with Seal, 7.3" Long, 50lb Tensile Strength, PA66/PA66HS, Black, 800/carton
Global Part Name	T50R0AH712PT1.5MD-PA66/EPDM/PA66HS-BK

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	7.3
Length L (Metric)	185.7
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.77
Bundle Diameter Max (Metric)	45.0
Thickness T (Imperial)	0.05

Thickness T (Metric)	1.2
Height H (Imperial)	0.64
Height H (Metric)	16.2
Panel Thickness Min (Imperial)	0.05
Panel Thickness Max (Imperial)	0.06
Panel Thickness Min (Metric)	1.4
Panel Thickness Max (Metric)	1.6
Mounting Hole Diameter D (Imperial)	0.28 x 0.47
Mounting Hole Diameter D (Metric)	7.0 x 12.0 mm
Mounting Hole Diameter D Min (Imperial)	0.28
Mounting Hole Diameter D Max (Imperial)	0.47
Mounting Hole Diameter D Max (Metric)	12.0
Disc Diameter (Metric)	20.0
Disc Diameter (Imperial)	0.79
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 (PA66) Ethylene Propylene Diene Terpolymer rubber free of Nitrosamine (EPDM)

Foot Part Material	PA66
Material Shortcut	PA66HS EPDM PA66
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	800
Package Quantity (Metric)	800
Customs Number	3926909988