

Specification Sheet

Part Number: WSM60IMHSUVH1

Design makes installation along frame rails fast and easy

Using weld stud eliminates the need for grinding down painted surfaces which saves time

Weld Stud eliminates need for stocking multiple sized metal P-Clamps which saves time and cost



Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg

Article Number 151-00146

Type WSM6

Color Black (BK)

Quantity Per bag

Product Description

When used in conjunction with a cable tie, the Weld Stud Mount significantly reduces time and labor, and eliminates the need for multiple sized P-clamps, nuts, and bolts. Simply weld the stud to the surface of any painted frame rail, and begin bundling with HellermannTyton cable ties. This eliminates the need in having to grind the surface in preparation. Adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.

Short Description	Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg
Global Part Name	WSM6-PA66HIRHSUV-BK
Length L (Imperial)	1.32
Length L (Metric)	33.5
Fixation Method	Stud Mount
Width W (Imperial)	1.07
Width W (Metric)	27.2
Height H (Imperial)	1.06
Height H (Metric)	27.0
Cable Tie Width Max (Imperial)	0.51
Cable Tie Width Max (Metric)	13.0
Stud Diameter (Metric)	6.0 mm
Stud Diameter (Imperial)	0.24
Material	Polyamide 6.6 high impact modified, heat and UV-resistant (PA66HIRHSUV)

Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988