


## Specification Sheet

Part Number: MB29M4



Compact size for areas with limited mounting space.

Simple to install with a screw or rivet.

Single hole attachment with two-way entry for cable tie.

Cable Tie Anchor Mount, 0.81 x .49", 0.193" Hole Dia, 0.18" Max Tie Width, PA66, Natural, 1000/pkg

Article Number 151-00297

Type MB2

Color Natural (NA)

Quantity Per bag

Product Description These cable tie mounts are compact in size. They are designed for simple yet robust installation particularly in areas with limited space. They pair with a cable tie for mounting applications including telecom equipment, switchgear and control cabinets.

Short Description Cable Tie Anchor Mount, 0.81 x .49", 0.193" Hole Dia, 0.18" Max Tie Width, PA66, Natural, 1000/pkg

Global Part Name MB2-PA66-NA

|                                       |                      |
|---------------------------------------|----------------------|
| Length L (Imperial)                   | 0.81                 |
| Length L (Metric)                     | 20.6                 |
| Fixation Method                       | Screw Mount          |
| Width W (Imperial)                    | 0.49                 |
| Width W (Metric)                      | 12.5                 |
| Cable Ties                            | T18 - T50            |
| Height H (Imperial)                   | .13                  |
| Height H (Metric)                     | 3.30                 |
| Cable Tie Width Max (Imperial)        | 0.18                 |
| Cable Tie Width Max (Metric)          | 4.6                  |
| Mounting Hole Diameter D (Imperial)   | 0.193                |
| Mounting Hole Diameter D (Metric)     | 4.9 mm               |
| Mounting Hole Diameter D Max (Metric) | 4.9                  |
| Material                              | Polyamide 6.6 (PA66) |
| Material Shortcut                     | PA66                 |

|                              |                                  |
|------------------------------|----------------------------------|
| Flammability                 | UL 94 V-2                        |
| Halogen Free                 | Yes                              |
| UV Resistant (Yes/No)        | No                               |
| Use Conditions               | For Indoor Use Only              |
| Operating Temperature        | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | No                               |
| ROHS Compliant               | Yes                              |
| Package Quantity (Imperial)  | 1000                             |
| Package Quantity (Metric)    | 1000                             |
| Customs Number               | 3926909988                       |