HellermannTyton

Specification Sheet

Part Number: 151-00786



HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.

An assortment of Connector Cips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Connector Clip with Round Fir Tree, 0.7-11.0 mm Panel Thick., 6.0 - 6.7 mm Hole Dia, PA66HIRHS, Black, 5000/box

Article Number 151-00786

Type CCFT6XLG

Color Black (BK)

Quantity Per bag

Product Description Connector Clips feature various attachment point configurations to

accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even

another harness assembly.

Short Description Connector Clip with Round Fir Tree, 0.7-11.0 mm Panel Thick., 6.0 - 6.7

mm Hole Dia, PA66HIRHS, Black, 5000/box

Length L (Imperial)	0.9
Length L (Metric)	23.0
Fixation Method	Fir tree for round holes
Width W (Metric)	16.1
Height H (Imperial)	0.95
Height H (Metric)	24.2
Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.43
Panel Thickness Min (Metric)	0.7
Panel Thickness Max (Metric)	11.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.26
Mounting Hole Diameter D (Metric)	6.0 - 6.7 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.7

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

UV Resistant (Yes/No) No

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3926909988