

Specification Sheet

Part Number: 151-01311

Bundling clip allows bundle to be parallel, perpendicular or offset from the panel and mounting hole for routing versatility.

Compact I-beam design provides a robust solution for all bundles, small to large.

Used in conjunction with HellermannTyton's 4x oval push pins, bundling clip prevents rotation of the bundle.

Oval hole can also be used as a portable hole joining two routings together.



Bundling Clip, 90 Deg with 6.5x12.5 Oval Hole, 40mm Long, PA66HIRHSUV, Black, 4000/ctn

Article Number 151-01311

Type TC90OVAL

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton's bundling clips allow a harness to be routed around a corner and attached to the panel at this location.

Short Description Bundling Clip, 90 Deg with 6.5x12.5 Oval Hole, 40mm Long, PA66HIRHSUV, Black, 4000/ctn

Global Part Name TC90OVAL-PA66HIRHSUV-BK

Length L (Imperial)	1.47
Length L (Metric)	37.3
Fixation Method	Bolt
Width W (Imperial)	0.59
Width W (Metric)	15.0
Height H (Imperial)	1.66
Height H (Metric)	40.8
Mounting Hole Diameter D (Imperial)	0.27 x 0.51
Mounting Hole Diameter D (Metric)	6.5 x 12.5 mm
Mounting Hole Diameter D Min (Imperial)	0.27
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	12.5
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV

Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988