

## Specification Sheet

Part Number: 151-02807

Connector clip meets USCAR EWCAP-005-17 clip slot specifications designed for large connectors, assuring compliance.

Non-rotating fir tree provides easy insertion with high extraction resistance for 9x17 mm oval holes.

Meets installation and extraction requirements of SAE/USCAR-2, delivering easy insertion with reliable performance.



USCAR Connector Clip with Oval Fir Tree, 17mm, 0.6-6.75mm Panel Thickness, PA66HIRHSUV, Black, 2500/ctn

Article Number 151-02807

Type CC17FT9X17

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description USCAR Connector Clip with Oval Fir Tree, 17mm, 0.6-6.75mm Panel Thickness, PA66HIRHSUV, Black, 2500/ctn

Global Part Name

CC17FT9X17-PA66HIRHSUV-BK

Length L (Imperial)	1.287
Length L (Metric)	32.7
Fixation Method	Fir Tree for oval holes
Width W (Imperial)	0.716
Width W (Metric)	18.2
Height H (Imperial)	0.789
Height H (Metric)	20.05
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.35 x 0.67
Mounting Hole Diameter D (Metric)	9.0 x 17.0 mm
Mounting Hole Diameter D Min (Imperial)	0.35
Mounting Hole Diameter D Max (Imperial)	0.35

Mounting Hole Diameter D Max (Metric) 9.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 2500

Package Quantity (Metric) 2500

Customs Number 3926909988