

Specification Sheet

Part Number: 151-02961

HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications.

Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.



HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Connector Clip with Oval Fir Tree, 17mm, Hole Dia, 8x15 mm, PA66HIRHSUV, Black, 2500/carton

Article Number 151-02961

Type CC17FT8X15

Color Black (BK)

Quantity Per box

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description	Connector Clip with Oval Fir Tree, 17mm, Hole Dia, 8x15 mm, PA66HIRHSUV, Black, 2500/carton
Global Part Name	CC17FT8X15-PA66HIRHSUV-BK
Length L (Imperial)	1.28
Length L (Metric)	32.7
Fixation Method	Fir Tree for oval holes
Width W (Imperial)	0.71
Width W (Metric)	18.2
Height H (Imperial)	0.77
Height H (Metric)	19.57
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.31 x 0.59
Mounting Hole Diameter D (Metric)	8.0 x 15.0 mm
Mounting Hole Diameter D Min (Imperial)	0.31

Mounting Hole Diameter D Max (Imperial) 0.31

Mounting Hole Diameter D Max (Metric) 8.0

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +230°F (-40°C to +110°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 2500

Package Quantity (Metric) 2500