

Specification Sheet

Part Number: 151-03076

The 90-degree configuration of this mini channel creates a solution for routing a wire harness around a corner



Design allows the mini channel to be used with a wide range of panel thicknesses and hole diameters

Mini Channel, 1.38" Long, 90° Angle, Fir Tree FT6B, PA66HIRHSUV, Black, 50/box

Article Number	151-03076
Type	BC90FT6B
Color	Black (BK)
Quantity Per	bag
Product Description	HellermannTyton's Bundling Clips create a solution that allows the harness to be routed around a corner and fixated into the panel at this location.
Short Description	Mini Channel, 1.38" Long, 90° Angle, Fir Tree FT6B, PA66HIRHSUV, Black, 50/box
Global Part Name	BC90FT6B-PA66HIRHSUV-BK

Length L (Imperial)	0.98
Length L (Metric)	25.0
Fixation Method	Fir Tree
Width W (Imperial)	0.06
Width W (Metric)	1.5
Height H (Imperial)	0.96
Height H (Metric)	24.5
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.22
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	5.5
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.9

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50