

Specification Sheet

Part Number: 151-03077

The 90-degree configuration of this mini channel creates a solution for routing a wire harness around a corner

Design allows the mini channel to be used with a wide range of panel thicknesses and hole diameters



Disc prevents rattling in high-vibration applications and protects against leakage and debris

Mini Channel, 1.38" Long, 90° Angle, Arrowhead, PA66HIRHSUV, Black, 50/pkg

Article Number 151-03077

Type BC90AH2

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's Bundling Clips create a solution that allows the harness to be routed around a corner, and fixated into the panel at this location.

Short Description Mini Channel, 1.38" Long, 90° Angle, Arrowhead, PA66HIRHSUV, Black, 50/pkg

Global Part Name BC90AH2-PA66HIRHSUV-BK

Length L (Imperial)	0.98
Length L (Metric)	25.0
Fixation Method	Arrowhead
Width W (Imperial)	0.06
Width W (Metric)	1.5
Height H (Imperial)	0.93
Height H (Metric)	23.6
Diameter D (Imperial)	0.50
Diameter D (Metric)	12.58
Panel Thickness Min (Imperial)	0.04
Panel Thickness Max (Imperial)	0.06
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	1.5
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.2 - 6.8 mm
Mounting Hole Diameter D Min (Imperial)	0.24

Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.8
Disc Diameter (Metric)	12.58
Disc Diameter (Imperial)	0.50
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)