

Specification Sheet

Part Number: 151-03099

Compact size fits most mounting applications.

Simple to install with screws or rivets.

Two-hole attachment with four-way entry for cable tie.

Low fire hazard materials comply with stringent NFPA 130 safety standards and improve opportunities to get product specified at the engineering stage of a project.



Screw Mount Cable Tie Base, 1.12 x 1.12", 0.18" Max Tie Width, 0.18" Hole Dia, PA666V0, Black, 100/pkg

Article Number 151-03099

Type MB4

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton screw fastened mounting bases are used with 18 through 50 lb cable ties to provide stability when securing bundles. Cable ties can be inserted parallel or perpendicular to the wire bundles. Low fire hazard material is designed specifically for rail applications.

Short Description Screw Mount Cable Tie Base, 1.12 x 1.12", 0.18" Max Tie Width, 0.18" Hole Dia, PA666V0, Black, 100/pkg

Global Part Name	MB4-PA666V0-BK
Length L (Imperial)	1.12
Length L (Metric)	28.5
Fixation Method	Screw Mount
Width W (Imperial)	1.12
Width W (Metric)	28.5
Cable Ties	T18 - T50
Height H (Imperial)	0.19
Height H (Metric)	4.8
Cable Tie Width Max (Imperial)	0.18
Cable Tie Width Max (Metric)	5.4
Mounting Hole Diameter D (Imperial)	0.18
Mounting Hole Diameter D (Metric)	4.6 mm
Mounting Hole Diameter D Max (Metric)	4.0
Mounting Hole Centers (Imperial)	0.8

Material	Polyamide 6.6/6, V0 (PA666V0)
Material Shortcut	PA666V0
Flammability	UL 94 V-0
Halogen Free	Yes
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Certification/Specification	Exova NFPA130: 2017 ASTM E 662 ASTM E 162 ASTM 1354
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988