

## Specification Sheet

Part Number: 151-03251



Easy assembly without the need of a tool.

Disc covers mounting hole and reduces vibration.

Fir tree mount provides easy insertion and excellent extraction resistance.

Push Pin w/Round Fir Tree, 0.6-12.5mm Panel Thickness, 6.1-6.7mm Dia, PPS, Bk, 5000/ctn

Article Number	151-03251
Type	FT6.5SDLGBPLUG
Color	Silver (SR)
Quantity Per	bag
Product Description	Push pins allow the fastening of multiple parts together with a simple press of the thumb.
Short Description	Push Pin w/Round Fir Tree, 0.6-12.5mm Panel Thickness, 6.1-6.7mm Dia, PPS, Bk, 5000/ctn
Global Part Name	FT6.5SDLGBPLUG-PPS-SR

Length L (Imperial)	0.84
Length L (Metric)	21.27
Fixation Method	Fir Tree
Width W (Imperial)	0.30
Width W (Metric)	7.80
Height H (Imperial)	0.84
Height H (Metric)	21.27
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.49
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	12.5
Mounting Hole Diameter D (Imperial)	0.24 - 0.26
Mounting Hole Diameter D (Metric)	6.1 - 6.7 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.7
Disc Diameter (Metric)	17

Disc Diameter (Imperial)	0.69
Material	Polyphenylene Sulfide (PPS)
Material Shortcut	PPS
Flammability	UL 94 V-0
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	No
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000