

Specification Sheet

Part Number: 151-03413

One-piece ratchet closure design allows for easy installation during pre- or final assembly.

Accommodates a range of diameters from 4-8 mm, reducing part inventory.

Compression limiter allows for high-torque fastening with an M8 bolt for a secure mounting option.

Clamp interior is designed to guide and center bundle to reduce pinching.

Easy-release feature allows for quick adjustments and maintenance.

Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.

Different mounting options available for various applications.



Mini Ratchet P-Clamp, 0.15 - 0.31" Bundle Dia., M8 Hole Dia., PA66HIRHSUV/ST/ZN, Black, 1000/carton

Article Number 151-03413

Type 4-8RCM8

Color Black (BK)

Quantity Per carton

| | |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | The Mini Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The clamp size and design make it an ideal P-clamp replacement for securing sensor wires, brake lines or other wires. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This release feature allows the clamp to be reused without removing or replacing any bolts or screws. |
| Short Description | Mini Ratchet P-Clamp, 0.15 - 0.31" Bundle Dia., M8 Hole Dia., PA66HIRHSUV/ST/ZN, Black, 1000/carton |
| Global Part Name | 4-8RCM8-PA66HIRHSUV-BK |
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 223 |
| Length L (Imperial) | 2.66 |
| Length L (Metric) | 67.7 |
| Fixation Method | Screw Mounting |
| Variant | Short |
| Width W (Imperial) | 0.69 |
| Width W (Metric) | 17.5 |
| Bundle Diameter Min (Imperial) | 0.15 |
| Bundle Diameter Min (Metric) | 3.81 |

| | |
|-------------------------------------|--------------------------------------------------------------------------|
| Bundle Diameter Max (Imperial) | 0.31 |
| Bundle Diameter Max (Metric) | 7.874 |
| Mounting Hole Diameter D (Imperial) | 0.33 |
| Mounting Hole Diameter D (Metric) | 8.4 mm |
| Stud Diameter (Metric) | M8 |
| Mounting Hole Centers (Imperial) | 0.98 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |

| | |
|-----------------------------|------------|
| Package Quantity (Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909988 |

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)