

Specification Sheet

Part Number: 151-03596



Fully enclosed clamp prevents slip, crush and fallout under vacuum.

Resistance against axial slide is 2.5x greater than competitor designs.

Tension arms allow for hose swelling of up to 12% .

Uses common MOC/LOC coupler for a large range of dual configurations.

Fir tree design meets USCAR44 standards.

LOC Locking Clamp, 38-43 mm, with 6.5 mm Fir Tree, PA66HIRHSUV, Black, 300/ctn

Article Number 151-03596

Type LOC38-43FT6.5

Color Black (BK)

Quantity Per carton

Product Description A robust clamp for radiator hoses and other large bundles that limits axial slide and rotation with fasteners that meet USCAR 44 testing standards and can be assembled to any MOC/LOC or omega clip.

Short Description LOC Locking Clamp, 38-43 mm, with 6.5 mm Fir Tree, PA66HIRHSUV, Black, 300/ctn

Global Part Name

LOC38-43FT6.5-PA66HIRHSUV-BK

Fixation Method

Fir Tree

Width W (Imperial)

3.50

Width W (Metric)

88.78

Bundle Diameter Min (Imperial)

1.5

Bundle Diameter Min (Metric)

38

Bundle Diameter Max (Imperial)

1.69

Bundle Diameter Max (Metric)

43

Height H (Imperial)

4.06

Height H (Metric)

103.18

Depth D (Imperial)

0.59

Depth D (Metric)

15.0

Mounting Hole Diameter D (Imperial)

0.24 - 0.26 (hexagonal) "0.24 - 0.28

Mounting Hole Diameter D (Metric)

6.1 - 7.0 mm 6.1 - 6.6 mm (hexagonal)

Mounting Hole Diameter D Min (Imperial)

0.24

Mounting Hole Diameter D Max (Imperial)

0.28

Mounting Hole Diameter D Max (Metric)	7.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	300
Package Quantity (Metric)	300
Customs Number	3926909988

