

## Specification Sheet

Part Number: 151-03625

One-piece ratchet closure design allows for easy installation during pre- or final assembly.

Fine-pitch ratchet increments enable precise sizing around multiple bundle diameters, reducing part inventory versus one-size clamps.

Easy-release feature allows for quick adjustments and maintenance without removal.



Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.

Mini Ratchet P-Clamp, 0.15 - 0.31" Bundle Dia., 6.5mm Hole Dia., PA66HIRHSUV, Black, 1000/carton

Article Number	151-03625
Type	4-8RC6.5PH
Color	Black (BK)
Quantity Per	carton

Product Description	The Mini Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The clamp size and design make it an ideal P-clamp replacement for securing sensor wires, brake lines or other wires. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This release feature allows the clamp to be reused without removing or replacing any bolts or screws.
Short Description	Mini Ratchet P-Clamp, 0.15 - 0.31" Bundle Dia., 6.5mm Hole Dia., PA66HIRHSUV, Black, 1000/carton
Global Part Name	4-8RC6.5PH-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	223
Length L (Imperial)	2.66
Length L (Metric)	67.7
Fixation Method	Screw Mounting
Variant	Short
Width W (Imperial)	0.69
Width W (Metric)	17.5
Bundle Diameter Min (Imperial)	0.15
Bundle Diameter Min (Metric)	3.81

Bundle Diameter Max (Imperial)	0.31
Bundle Diameter Max (Metric)	7.874
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.5 mm
Mounting Hole Centers (Imperial)	0.98
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988