

## Specification Sheet

Part Number: 151-03967

Two clamps with 360-degree enclosures ensure both bundles are secure when being routed.

Clamp can be opened for bundle maintenance.

Long 6.5 mm fir tree allows clip to be installed in panels up to 6 mm thick and for hole sizes from 6.1-6.9 mm.



Dual LOC Locking Clamp, 18-22 mm, with 6.5 mm Fir Tree, PA66HIRHSUV, Black, 700/ctn

Article Number 151-03967

Type DBLEClamp18-22FT6.5

Color Black (BK)

Quantity Per carton

Product Description Designed for coupling and mounting double routings, this clamp features HellermannTyton's LOC with a 6.5 mm fir tree.

Short Description Dual LOC Locking Clamp, 18-22 mm, with 6.5 mm Fir Tree, PA66HIRHSUV, Black, 700/ctn

Global Part Name DBLEClamp18-22FT6.5-PA66HIRHSUV-BK

Length L (Imperial)	2.58
Length L (Metric)	65.5
Fixation Method	Fir Tree
Width W (Imperial)	2.58
Width W (Metric)	65.5
Bundle Diameter Min (Imperial)	0.71
Bundle Diameter Min (Metric)	18.0
Bundle Diameter Max (Imperial)	0.87
Bundle Diameter Max (Metric)	22.0
Height H (Imperial)	1.62
Height H (Metric)	41.1
Depth D (Imperial)	0.79
Depth D (Metric)	20.0
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.24
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0

Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.9
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial) 700

Package Quantity (Metric) 700

Customs Number 3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)