

## Specification Sheet

Part Number: 151-03992

Stud mount clamp secures bundles above a bolt or stud.

Two clamps with 360-degree enclosures ensure both bundles are secure when being routed.

Clamp can be opened for bundle maintenance.



Dual LOC Locking Clamp, 18-22 mm Clamp, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 800/ctn

Article Number	151-03992
Type	DLOC5-22SBM5-6
Color	Black (BK)
Quantity Per	carton
Product Description	Designed for coupling and mounting double routings, this clamp features HellermannTyton's LOC with a best-in-class stud mount to secure to a 5 mm or 6 mm stud or bolt. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point.
Short Description	Dual LOC Locking Clamp, 18-22 mm Clamp, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 800/ctn
Global Part Name	DLOC5-22SBM5-6-PA66HIRHSUV-BK

Length L (Imperial)	2.58
Length L (Metric)	65.5
Fixation Method	Stud Mount
Width W (Imperial)	2.58
Width W (Metric)	65.5
Bundle Diameter Min (Imperial)	0.71
Bundle Diameter Min (Metric)	18.0
Bundle Diameter Max (Imperial)	0.87
Bundle Diameter Max (Metric)	22.0
Height H (Imperial)	1.07
Height H (Metric)	27.2
Depth D (Imperial)	0.79
Depth D (Metric)	20.0
Stud Diameter (Metric)	5.0 mm 6.0 mm
Stud Diameter (Imperial)	M5, M6, T5, T6

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	800
Package Quantity (Metric)	800
Customs Number	3926909988