

## Specification Sheet

Part Number: 151-04060



TPE layer protects cables and prevents rotation and axial slide, for a positive hold without crushing bundles.

Clamps are stackable to minimize space.

Releasable latch allows access to routings for serviceability.

Dual Bundle High Voltage Clamp, 0.75" Bundle Dia, PA66GF15%/TPE, Black, 400/carton

Article Number	151-04060
Type	HDC19X2BASE
Color	Black (BK)
Quantity Per	carton
Product Description	A clamp system that protects high-voltage cables in dual routing configurations and can be secured using hardware.
Short Description	Dual Bundle High Voltage Clamp, 0.75" Bundle Dia, PA66GF15%/TPE, Black, 400/carton
Global Part Name	HDC19X2BASE-PA66GF15/TPE-BK

Length L (Imperial)	3.24
Length L (Metric)	82.3
Width W (Imperial)	1.02
Width W (Metric)	26.0
Bundle Diameter Min (Imperial)	0.73
Bundle Diameter Min (Metric)	18.5
Bundle Diameter Max (Imperial)	0.77
Bundle Diameter Max (Metric)	19.5
Bundle Diameter 1st Loop Max (Imperial)	0.77
Bundle Diameter 1st Loop Max (Metric)	19.5
Bundle Diameter 2nd Loop Max (Imperial)	0.77
Bundle Diameter 2nd Loop Max (Metric)	19.5
Height H (Imperial)	1.31
Height H (Metric)	33.2
Mounting Hole Diameter D (Imperial)	0.31 x 0.05
Mounting Hole Diameter D (Metric)	M8 x 1.25 Threaded

Material	Polyamide 6.6 glass fiber reinforced (PA66GF15%) Thermoplastic Elastomer (TPE)
Material Shortcut	TPE PA66GF15
Flammability	UL 94 HB
Halogen Free	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	400
Package Quantity (Metric)	400
Customs Number	3926909988