

Specification Sheet

Part Number: 151-04061



TPE layer protects cables and prevents rotation and axial slide, for a positive hold without crushing bundles.

Clamps are stackable to minimize space.

Releasable latch allows access to routings for serviceability.

Triple Bundle High Voltage Clamp, 0.67" Bundle Dia, PA66GF15%/TPE, Black, 350/carton

Article Number	151-04061
Type	HDC17X3BASE
Color	Black (BK)
Quantity Per	carton
Product Description	A clamp system that protects high-voltage cables in triple routing configurations and can be secured using hardware.
Short Description	Triple Bundle High Voltage Clamp, 0.67" Bundle Dia, PA66GF15%/TPE, Black, 350/carton
Global Part Name	HDC17X3BASE-PA66GF15/TPE-BK

Length L (Imperial)	4.97
Length L (Metric)	126.3
Width W (Imperial)	1.02
Width W (Metric)	26.0
Bundle Diameter Min (Imperial)	0.65
Bundle Diameter Min (Metric)	16.5
Bundle Diameter Max (Imperial)	0.69
Bundle Diameter Max (Metric)	17.5
Bundle Diameter 1st Loop Max (Imperial)	0.69
Bundle Diameter 1st Loop Max (Metric)	17.5
Bundle Diameter 2nd Loop Max (Imperial)	0.69
Bundle Diameter 2nd Loop Max (Metric)	17.5
Height H (Imperial)	1.31
Height H (Metric)	33.2
Mounting Hole Diameter D (Imperial)	0.31 x 0.05
Mounting Hole Centers (Imperial)	1.73

Material	Thermoplastic Elastomer (TPE) Polyamide 6.6 glass fiber reinforced (PA66GF15%)
Material Shortcut	PA66GF15 TPE
Flammability	UL 94 HB
Halogen Free	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	350
Package Quantity (Metric)	350
Customs Number	3926909988