

## Specification Sheet

Part Number: 151-04266



These connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications.

Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.

A wide assortment of styles is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Connector Clip with Oval Fir Tree, 9.0 - 17.0mm Hole Dia, PA66HIRHS, Natural, 3000/carton

Article Number	151-04266
----------------	-----------

Type	CC18
------	------

Color	Natural (NA)
-------	--------------

Quantity Per	carton
--------------	--------

Product Description	HellermannTyton Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
---------------------	---

Short Description	Connector Clip with Oval Fir Tree, 9.0 - 17.0mm Hole Dia, PA66HIRHS, Natural, 3000/carton
-------------------	---

Global Part Name	CC18-PA66HIRHS-NA
------------------	-------------------

Minimum Tensile Strength (Imperial)	35
-------------------------------------	----

Minimum Tensile Strength (Metric)	155
-----------------------------------	-----

Length L (Imperial)	1.19
---------------------	------

Length L (Metric)	30.29
-------------------	-------

Fixation Method	Fir Tree for oval holes
-----------------	-------------------------

Width W (Imperial)	0.80
--------------------	------

Width W (Metric)	20.32
------------------	-------

Height H (Imperial)	0.93
---------------------	------

Height H (Metric)	23.57
-------------------	-------

Panel Thickness Min (Imperial)	0.02
--------------------------------	------

Panel Thickness Max (Imperial)	0.37
--------------------------------	------

Panel Thickness Min (Metric)	0.6
------------------------------	-----

Panel Thickness Max (Metric)	9.5
------------------------------	-----

Mounting Hole Diameter D (Imperial)	0.35 x 0.67
-------------------------------------	-------------

Mounting Hole Diameter D (Metric)	9.0 x 17.0 mm
-----------------------------------	---------------

Mounting Hole Diameter D Min (Imperial) 0.35

Mounting Hole Diameter D Max (Imperial) 0.35

Mounting Hole Diameter D Max (Metric) 9.0

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +230°F (-40°C to +110°C)

Reach Compliant (Article 33) No

Package Quantity (Imperial) 3000

Package Quantity (Metric) 3000

Customs Number 3926909988

