

## Specification Sheet

Part Number: 156-00459



Versatile design allows cable routing above, perpendicular or parallel to stud.

Can mount up to three bundles simultaneously, making efficient use of a single mounting point.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.

PA46 material option allows use in high-heat applications.

2-Piece Cable Tie with Stud Mount, 8.0"L, 5mm Stud Mount, 50lb Tensile Strength, PA66HS/PA66HIRHS, NA/BK, 500/pkg

|                |                         |
|----------------|-------------------------|
| Article Number | 156-00459               |
| Type           | T50RSBH5-10             |
| Color          | Natural (NA) Black (BK) |
| Quantity Per   | bag                     |

**Product Description**

Unique, two-piece design allows routing to be above, parallel or perpendicular to stud. This also enables up to three separate bundles to be fastened to the same stud. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

|                                |   |
|--------------------------------|---|
| Short Description              | 2-Piece Cable Tie with Stud Mount, 8.0"L, 5mm Stud Mount, 50lb Tensile Strength, PA66HS/PA66HIRHS, NA/BK, 500/pkg |
| Global Part Name               | T50RSBH5-10-PA66HS/PA66HIRHS-NA/BK  |
| Length L (Metric)              | 200.0   |
| Fixation Method                | Weld Stud Fixing  |
| Identification Plate Position  | none  |
| Tie Closure                    | plastic pawl  |
| Variant                        | Inside Serrated   |
| Width W (Metric)               | 4.6   |
| Bundle Diameter Max (Imperial) | 1.77  |
| Bundle Diameter Max (Metric)   | 45.0  |
| Thickness T (Metric)           | 1.2   |
| Disc Diameter (Metric)         | 25.0  |
| Stud Diameter (Metric)         | M5 T5   |
| Stud Diameter (Imperial)       | 0.20  |

|                              |  |
|------------------------------|--|
| Material                     | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)<br>Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut            | PA66HS PA66HIRHS   |
| UV Resistant (Yes/No)        | No   |
| Use Conditions               | For Indoor and Outdoor Use   |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)  |
| Reach Compliant (Article 33) | Yes  |
| ROHS Compliant               | Yes  |
| Package Quantity (Imperial)  | 500  |
| Package Quantity (Metric)    | 500  |
| Customs Number               | 3926909988   |

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)