

Specification Sheet

Part Number: 156-00911



Head allows for a .2" lateral adjustment on stud during installation.

Quick and easy installation ideal for manufacturing environment.

2-Piece Cable Tie/Oval Stud Mount, 11.8" Long, 50lb Tensile Strength, PA66HIRHS, Black, 250/pkg

Article Number	156-00911
Type	T50ISBS520-40
Color	Black (BK)
Quantity Per	bag
Product Description	Oval Shaped Stud Mount's special design allows for a .2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.
Short Description	2-Piece Cable Tie/Oval Stud Mount, 11.8" Long, 50lb Tensile Strength, PA66HIRHS, Black, 250/pkg
Global Part Name	T50ISBS520-40-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	222
Length L (Imperial)	11.8
Length L (Metric)	300.0
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.79
Bundle Diameter Min (Metric)	20.0
Bundle Diameter Max (Imperial)	1.57
Bundle Diameter Max (Metric)	40.0
Stud Length Min (Imperial)	0.56
Stud Length Min (Metric)	14.2

Stud Diameter (Metric)	5.0 mm
Stud Diameter (Imperial)	0.20
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HS PA66HIRHS
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	250
Package Quantity (Metric)	250
Customs Number	3926909988