

Specification Sheet

Part Number: 156-00940

Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

Cable tie is outside serrated to reduce bundle chafing.



2-Piece Cable Tie & Edge Clip, 8.0" Long, EC4B, 1 - 3 mm Panel, 50lb, PA66HS, Natural, 500/pkg

Article Number 156-00940

Type T50REC4B

Color Black (BK) Natural (NA)

Quantity Per bag

Product Description The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

| | |
|-------------------------------------|--|
| Short Description | 2-Piece Cable Tie & Edge Clip, 8.0" Long, EC4B, 1 - 3 mm Panel, 50lb, PA66HS, Natural, 500/pkg |
| Global Part Name | T50REC4B-PA66HS/PA66HIRHS-NA/BK |
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 8.0 |
| Length L (Metric) | 202.0 |
| Fixation Method | Edge Clip |
| Identification Plate Position | none |
| Releasable Closure | No |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.18 |
| Width W (Metric) | 4.6 |
| Bundle Diameter Min (Imperial) | 0.16 |
| Bundle Diameter Min (Metric) | 4.0 |
| Bundle Diameter Max (Imperial) | 1.77 |
| Bundle Diameter Max (Metric) | 45.0 |

| | |
|--------------------------------|---|
| Thickness T (Imperial) | 0.05 |
| Thickness T (Metric) | 1.2 |
| Height H (Imperial) | 0.63 |
| Height H (Metric) | 16.0 |
| Panel Thickness Min (Imperial) | 0.04 |
| Panel Thickness Max (Imperial) | 0.12 |
| Panel Thickness Min (Metric) | 1.0 |
| Panel Thickness Max (Metric) | 3.0 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut | PA66HIRHS PA66HS |
| Material Cable Tie | Polyamide 6.6 heat stabilized (PA66HS) |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) -40°F to +230°F (-40°C to +110°C) |

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)