

Specification Sheet

Part Number: 156-01571



Head allows for a 0.2" lateral adjustment on stud during installation.

Quick and easy installation ideal for manufacturing environment.

2-Piece M6 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HIRHSUV/POM, BK, 2000/ctn

Article Number	156-01571
Type	T50R0SBL6UM90SET
Color	Black (BK)
Quantity Per	bag
Product Description	Oval shaped stud mount's special design allows for a 0.2" (5.5mm) lateral adjustment in case of misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.
Short Description	2-Piece M6 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HIRHSUV/POM, BK, 2000/ctn
Global Part Name	T50R0SBL6UM90SET-PA66HIRHSUV/POM-BK

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	0.67
Length L (Metric)	17.02
Fixation Method	Stud Mount
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.46
Width W (Metric)	11.72
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.98
Height H (Metric)	25.0

Mounting Hole Diameter D (Metric)	M6 x 1
Stud Diameter (Metric)	6.0 mm
Stud Diameter (Imperial)	0.24
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyacetal (POM)
Foot Part Material	POM
Material Shortcut	PA66HIRHSUV POM
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-22°F to +194°F (-30°C to +90°C) -40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial) 2000

Package Quantity (Metric) 2000

Customs Number 3926909988