

Specification Sheet

Part Number: 156-01665



Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation.

Fir tree is easy to insert, reducing operator strain, yet demonstrates high extraction resistance.

2-Piece Cable Tie/Rotated Fir Tree Mount, 4x Oval Fir Tree, PA66HIRHSUV, Black, 1000/ctn

Article Number 156-01665

Type T50ROVALAPILLAR-SET

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton's combination cable tie fir tree mounts provide reliable bundling and a secure grip into a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are engineered to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie, providing separation between bundles to prevent chafing and abrasion.

Short Description 2-Piece Cable Tie/Rotated Fir Tree Mount, 4x Oval Fir Tree, PA66HIRHSUV, Black, 1000/ctn

Global Part Name

T50ROVALAPILLAR-SET-PA66HS/PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	1.80
Length L (Metric)	45.7
Fixation Method	Fir Tree
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.79
Width W (Metric)	20.0
Bundle Diameter Min (Imperial)	0.2
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Height H (Imperial)	1.40
Height H (Metric)	35.5
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 ";0.26 x 0.49 ";0.26 x 0.51 ";0.28 x 0.47
Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm 6.5 x 12.5 mm 6.5 x 13.0 mm 7.0 x 12.0 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	7.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS PA66HIRHSUV

UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C) -40°F to +257°F (-40°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	300
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)