

Specification Sheet

Part Number: 156-02462

Versatile and robust fir tree design provides low insertion effort yet delivers exceptional retention strength in an 8 mm hole and M10 threaded hole.

Wider and thinner strap design increases flexibility and minimizes pinching of bundles, hoses and tubing.

PA46 nylon material provides great performance at up to 135°F continuous operating temperature.



2-Piece Cable Tie/Fir Tree Mount, 8mm Hole and M10 Threaded Hole, PA66HIRHSUV, BK, 1200/ctn

Article Number 156-02462

Type WSSDFTM10WSSDSET

Color Black (BK)

Quantity Per bag

Product Description These two-piece fasteners are pre-assembled and offer a simple and versatile method of bundling and mounting cables. Sold as an unassembled set, this oval fir tree and tie combination allows the user to install the tie in two different directions, securing the bundle perpendicular or inline to the oval mounting hole.

Short Description 2-Piece Cable Tie/Fir Tree Mount, 8mm Hole and M10 Threaded Hole, PA66HIRHSUV, BK, 1200/ctn

Global Part Name

WSSDFTM10WSSDSET-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

120

Minimum Tensile Strength (Metric)

533

Length L (Imperial)

9.1

Length L (Metric)

231.14

Fixation Method

Fir tree for round holes

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.88

Width W (Metric)

22.6

Bundle Diameter Min (Imperial)

0.37

Bundle Diameter Min (Metric)

9.4

Bundle Diameter Max (Imperial)

2.25

Bundle Diameter Max (Metric)

57.15

Height H (Imperial)	0.98
Height H (Metric)	23.7
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.23
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.3 - 0.33
Mounting Hole Diameter D (Metric)	7.6 - 8.4 mm M10 Threaded
Mounting Hole Diameter D Min (Imperial)	0.3
Mounting Hole Diameter D Max (Imperial)	0.33
Mounting Hole Diameter D Max (Metric)	8.4
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes

UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	1200
Package Quantity (Metric)	1200
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)