

Specification Sheet

Part Number: 156-02482



Anti-rotation pin eliminates movement of bundle when fastening bolt.

Heavy duty mount with robust 120 lb tie delivers an ultra strong alternative to metal clamps.

Assembly withstands vibrations and displacement forces.

Metal bushing accommodates high tightening torque.

2-Piece Cable Tie/Screw Mount, Unassembled Set, 15" L, M8 Hole, 120lb, PA66HIRHS, Black, 1000/ctn

Article Number	156-02482
Type	T120RCPCM8-TSSET
Color	Black (BK)
Quantity Per	carton
Product Description	These heavy duty cable tie mounts, secured with mechanical fasteners, include an anti-rotation pin that keeps the mount and harness assembly in position during the torquing of the bolt or nut. They provide an attachment point for securing and routing a single bundle. The mounts provide the highest level of fastening for critical cable security.
Short Description	2-Piece Cable Tie/Screw Mount, Unassembled Set, 15" L, M8 Hole, 120lb, PA66HIRHS, Black, 1000/ctn

Global Part Name T120RCPCM8-TSSET-PA66HIRHSUV/PA66HIRHS-BK

Minimum Tensile Strength (Imperial) 120

Minimum Tensile Strength (Metric) 535

Length L (Imperial) 15.0

Length L (Metric) 385.0

Fixation Method Screw Mount

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.30

Width W (Metric) 7.6

Bundle Diameter Min (Imperial) 0.2

Bundle Diameter Min (Metric) 5.0

Bundle Diameter Max (Imperial) 4.13

Bundle Diameter Max (Metric) 105.0

Thickness T (Imperial)	0.07
Thickness T (Metric)	1.8
Height H (Imperial)	0.92
Height H (Metric)	23.5
Mounting Hole Diameter D (Imperial)	0.33
Mounting Hole Diameter D (Metric)	8.4 mm
Mounting Hole Diameter D Max (Metric)	8.5
Stud Diameter (Metric)	8.0 mm
Stud Diameter (Imperial)	0.31
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Foot Part Material	PA66HIRHSUV
Material Shortcut	PA66HIRHS PA66HIRHSUV
Material Cable Tie	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Flammability	UL 94 HB
Halogen Free	Yes

UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)