

## Specification Sheet

Part Number: 156-02962



Connector clip design meets USCAR EWCAP-005-11 clip slot specifications, assuring compliance.

Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound.

Sealed arrowhead meets USCAR44 push in, pull off and sealing standards.

Tape Clip w/Arrowhead Mount and 11 mm Connector Clip Slot, POM/TPE, Natural/Gray, 1000/carton

Article Number	156-02962
Type	BC28OSSRAH1.4T
Color	Gray (GY) Natural (NA)
Quantity Per	box
Product Description	Offset tape clip with round arrowhead mount and seal is ideal for ingress applications. The arrowhead stays firmly locked into place when fully inserted into the hole.
Short Description	Tape Clip w/Arrowhead Mount and 11 mm Connector Clip Slot, POM/TPE, Natural/Gray, 1000/carton
Global Part Name	BC28OSSRAH1.4T-POM/TPE-GY/NA

Length L (Imperial)	1.97
Length L (Metric)	50.0
Offset Length (Imperial)	1.25
Offset Length (Metric)	31.8
Width W (Imperial)	1.96
Width W (Metric)	49.8
Height H (Imperial)	0.59
Height H (Metric)	15.1
Panel Thickness Min (Imperial)	0.05
Panel Thickness Max (Imperial)	0.07
Panel Thickness Min (Metric)	1.2
Panel Thickness Max (Metric)	1.8
Mounting Hole Diameter D (Imperial)	0.24 - 0.27
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27

Mounting Hole Diameter D Max (Metric) 6.9

Disc Diameter (Metric) 22.3

Disc Diameter (Imperial) 0.88

Material Thermoplastic Elastomer (TPE) Polyacetal (POM)

Material Shortcut POM TPE

Flammability UL 94 HB

UV Resistant (Yes/No) Yes

Use Conditions For Indoor Use Only

Operating Temperature -40°F to +194°F (-40°C to +90°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)