

Specification Sheet

Part Number: 156-02995

Versatile design allows cable routing above, perpendicular or parallel to stud.

Can mount up to three bundles simultaneously, making efficient use of a single mounting point.

Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.



2-Piece M14 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HIRHSUV, BK, 1000/pkg

Article Number 156-02995

Type T50R0SBS14SET

Color Black (BK)

Quantity Per carton

Product Description Unique, two-piece cable tie and stud mount combination allows routing to be above, parallel or perpendicular to stud. This also enables up to three separate bundles to be fastened to the same stud. With its low insertion force and high extraction performance, HellermannTyton's mounting tie offers the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description 2-Piece M14 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HIRHSUV, BK, 1000/pkg

Global Part Name T50R0SBS14SET-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 223

Length L (Imperial) 8.0

Length L (Metric) 203.2

Fixation Method Stud Mount

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 1.33

Width W (Metric) 34.0

Bundle Diameter Min (Imperial) 0.39

Bundle Diameter Min (Metric) 10.0

Bundle Diameter Max (Imperial) 1.77

Bundle Diameter Max (Metric) 45.0

Cable Ties T50R, T120R0HSH4

Height H (Imperial)	0.82
Height H (Metric)	21.0
Mounting Hole Diameter D (Metric)	M14
Stud Diameter (Metric)	14.0 mm
Stud Diameter (Imperial)	0.55
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Foot Part Material	PA66HIRHSUV
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)