

Specification Sheet

Part Number: 156-03014

Three-piece wide strap tie and coupler assembly bundles and separates two routings at any angle from parallel to 90 degrees from each other.

Wide strap ties minimize pinching of soft hoses and convoluted tubing, while the coupler protects routings from friction and abrasion.

Space-saving coupler means more room for routings.

3-Piece Wide Strap Tie with Coupler, 15.1" Long, 0.37" - 4.12" Dia, 120lbs, PA66HIRHSUV, Black, 100/bg

Article Number 156-03014

Type DUALWSRASSY

Color Black (BK)

Quantity Per bag

Product Description Couplers simplify connecting two cable ties for routing and separating

bundles. Designed to allow up to 90 degrees of rotation, these

assemblies are ideal for applications in which the bundle, pipe or hose

requires slight movement in relation to the fastening point.

Short Description 3-Piece Wide Strap Tie with Coupler, 15.1" Long, 0.37" - 4.12" Dia,

120lbs, PA66HIRHSUV, Black, 100/bg

Global Part Name DUALWSRASSY-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)	120
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	15.1
Length L (Metric)	383.0
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.5
Width W (Metric)	12.7
Bundle Diameter Min (Imperial)	0.59
Bundle Diameter Min (Metric)	15.0
Bundle Diameter Max (Imperial)	3.86
Bundle Diameter Max (Metric)	98.0
Height H (Imperial)	0.43
Height H (Metric)	10.86

Material Polyamide 6.6 high impact modified, heat and UV stabilized

(PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

UV Resistant (Yes/No) Yes

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

© 2024 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions