

Specification Sheet

Part Number: 156-03169

Cable tie and mount combination eliminates the need for multiple-sized fixed-diameter clamps.

Soft TPE inner layer inhibits lateral movements on the bundle, especially on smooth tubing

Pre-locking feature holds the cable tie in place before it is tensioned.

Soft-grip cable ties can be removed with a screwdriver for maintenance.



2-Pc. Soft-Grip Tie/Heavy Duty Mount, Unassembled Set, PA66HIRHSUV/TPE, Black/Blue, 500/ctn

Article Number	156-03169
Type	SGT100SHDM320SET
Color	Black (BK) Blue (BU)
Quantity Per	bag
Product Description	The Soft-Grip Cable Tie features a pliable TPE layer that protects sensitive wire bundles and tubes. The cable tie maintains a high tensile strength and low insertion force. Arrowhead and heavy duty mount options provide an all-in-one bundling and mounting solution.
Short Description	2-Pc. Soft-Grip Tie/Heavy Duty Mount, Unassembled Set, PA66HIRHSUV/TPE, Black/Blue, 500/ctn

Global Part Name SGT100SHDM320SET-PA66HIRHSUV/TPE-BK/BU

Minimum Tensile Strength (Imperial) 71

Minimum Tensile Strength (Metric) 315

Length L (Imperial) 5.51

Length L (Metric) 140.0

Fixation Method Screw Mount

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.5

Width W (Metric) 12.7

Bundle Diameter Min (Imperial) 0.39

Bundle Diameter Min (Metric) 10.0

Bundle Diameter Max (Imperial) 1

Bundle Diameter Max (Metric) 25.4

Height H (Imperial)	0.81
Height H (Metric)	20.7
Mounting Hole Diameter D (Imperial)	0.33
Mounting Hole Diameter D (Metric)	8.31 mm
Mounting Hole Diameter D Max (Metric)	8.31
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Thermoplastic Elastomer (TPE)
Foot Part Material	PA66HIRHSUV
Material Shortcut	TPE PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL 94 HB
Halogen Free	No
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No

ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988