

Specification Sheet

Part Number: 156-03181



Mount is designed to provide a low push-in force and high pull-out resistance.

Disc feature prevents rattling in high-vibration applications and protects against debris ingress.

Heavy-duty tie design offers higher tensile strength.

Mount design ideal for 8 mm or threaded M10 holes.

2-Piece Cable Tie/Fir Tree Mount, Unassembled Set, 9"L, FT8/M10 Hole, PA66HIRHSUV, Black, 1000/ctn

| | |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number | 156-03181 |
| Type | T120SFT8M10SET |
| Color | Black (BK) |
| Quantity Per | carton |
| Product Description | HellermannTyton's fir tree mount provides a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. It is sold as an unassembled set with the cable tie. |
| Short Description | 2-Piece Cable Tie/Fir Tree Mount, Unassembled Set, 9"L, FT8/M10 Hole, PA66HIRHSUV, Black, 1000/ctn |
| Global Part Name | T120SFT8M10SET-PA66HIRHSUV-BK |

| | |
|-------------------------------------|--------------------------|
| Minimum Tensile Strength (Imperial) | 120 |
| Minimum Tensile Strength (Metric) | 535 |
| Length L (Imperial) | 9.0 |
| Length L (Metric) | 229.0 |
| Fixation Method | Fir tree for round holes |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.30 |
| Width W (Metric) | 7.6 |
| Bundle Diameter Min (Imperial) | 0.2 |
| Bundle Diameter Min (Metric) | 5.0 |
| Bundle Diameter Max (Imperial) | 2.17 |
| Bundle Diameter Max (Metric) | 55.0 |
| Height H (Imperial) | 0.90 |

| | |
|-----------------------------------------|--------------------------------------------------------------------------|
| Height H (Metric) | 22.77 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.24 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 6.0 |
| Mounting Hole Diameter D (Imperial) | 0.315 |
| Mounting Hole Diameter D (Metric) | 8.0 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.299 |
| Mounting Hole Diameter D Max (Imperial) | 0.331 |
| Mounting Hole Diameter D Max (Metric) | 8.4 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Foot Part Material | PA66HIRHSUV |
| Material Shortcut | PA66HIRHSUV |
| Material Cable Tie | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Flammability | UL 94 HB |

| | |
|------------------------------|-----------------------------------|
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909988 |

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)