

Specification Sheet

Part Number: 156-03182



Keeps three bundles separated and parallel to one another.

Preassembled cable tie on bracket for easier installation.

2-Piece Triple Bracket Separator, Outside Serrated 120 lb Tie, 0.98" Max Dia., PA66HIRHSUV, Blk, 250/ctn

Article Number 156-03182

Type T120Triple25

Color Black (BK)

Quantity Per carton

Product Description The two-piece triple bracket separator mounts three bundles with a T120 outside-serrated cable tie. This product can be used for alternating current (AC) lines or with direct current (DC) lines that need to include a ground cable or adjacent cooling line.

Short Description 2-Piece Triple Bracket Separator, Outside Serrated 120 lb Tie, 0.98" Max Dia., PA66HIRHSUV, Blk, 250/ctn

Global Part Name T120TRIPLE25-PA66HIRHSUV-BK

| | |
|---|------|
| Minimum Tensile Strength (Imperial) | 120 |
| Minimum Tensile Strength (Metric) | 535 |
| Length L (Imperial) | 3.78 |
| Length L (Metric) | 96.0 |
| Identification Plate Position | none |
| Width W (Imperial) | 1.15 |
| Width W (Metric) | 29.0 |
| Bundle Diameter Max (Imperial) | 0.98 |
| Bundle Diameter Max (Metric) | 25 |
| Bundle Diameter 1st Loop Max (Imperial) | 0.98 |
| Bundle Diameter 1st Loop Max (Metric) | 25 |
| Bundle Diameter 2nd Loop Max (Imperial) | 0.98 |
| Bundle Diameter 2nd Loop Max (Metric) | 25 |
| Height H (Imperial) | 1.46 |
| Height H (Metric) | 37.0 |

| | |
|------------------------------|--|
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Foot Part Material | PA66HIRHSUV |
| Material Shortcut | PA66HIRHSUV |
| Material Cable Tie | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| UV Resistant (Yes/No) | Yes |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 250 |
| Package Quantity (Metric) | 250 |
| Customs Number | 3926909988 |