

Specification Sheet

Part Number: 156-03218

Made from 100% post-industrial recycled material, this product delivers the same elevated performance as our products made from standard impact-modified, heat-stabilized material.

The ReSource family of products helps companies meet their sustainability goals.

All-in-one bundling and fastening solution reduces costs and assembly time.

Fir tree provides low insertion effort yet demonstrates high extraction resistance.



2-Piece Cable Tie/Oval Fir Tree, Unassembled Set, 8.0"L, 6.2 x 12.2 mm;6.5 x 12.5 mm;6.5 x 13.0 mm or 7.0 x 12.0 mm Mounting Hole, PA66HIRHS(REC100), Black, 3000/ctn

Article Number 156-03218

Type T50RSADFTOVALSET

Color Black (BK)

Quantity Per carton

Product Description Part of our sustainable line of products, the ReSource product family features solutions made from excess plastic left over from the manufacturing process or from consumers. This fir tree mount is made from 100 percent postindustrial recycled plastic. It provides a secure grip in a mounting hole. The fir tree provides a low push-in force and high pull-out resistance. The mount can slide along the cable tie to adjust orientation as needed. The mount is sold as an assembly with the cable tie.

| | |
|-------------------------------------|---|
| Short Description | 2-Piece Cable Tie/Oval Fir Tree, Unassembled Set, 8.0"L, 6.2 x 12.2 mm;6.5 x 12.5 mm;6.5 x 13.0 mm or 7.0 x 12.0 mm Mounting Hole, PA66HIRHS(REC100), Black, 3000/ctn |
| Global Part Name | T50RSADFTOVALSET-PA66HIRHS(REC100)-BK |
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 8.0 |
| Length L (Metric) | 202.0 |
| Fixation Method | Fir Tree |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.69 |
| Width W (Metric) | 17.63 |
| Bundle Diameter Min (Imperial) | 0.2 |
| Bundle Diameter Min (Metric) | 5.0 |

| | |
|---|--|
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Height H (Imperial) | 0.787 |
| Height H (Metric) | 20.0 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.24 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 6.0 |
| Mounting Hole Diameter D (Imperial) | 0.24 x 0.48 " 0.26 x 0.49 " 0.26 x 0.51 " 0.28 x 0.47 |
| Mounting Hole Diameter D (Metric) | 6.5 x 12.5 mm 6.2 x 12.2 mm 6.5 x 13.0 mm 7.0 x 12.0 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.51 |
| Mounting Hole Diameter D Max (Metric) | 7.0 |
| Material | Polyamide 6.6 recycled, high impact modified, heat stabilized (PA66HIRHS(REC100)) |
| Foot Part Material | PA66HIRHS(REC100) |

| | |
|-----------------------------|---|
| Material Shortcut | PA66HIRHS(REC100) |
| Material Cable Tie | Polyamide 6.6 recycled, high impact modified, heat stabilized (PA66HIRHS(REC100)) |
| Flammability | UL 94 HB |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 3000 |
| Package Quantity (Metric) | 3000 |
| Customs Number | 3926909988 |