

Specification Sheet

Part Number: 156-03301



Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Independent rotation allows for adjustable routing orientation.

MOC Clip, 5 mm dia, 5 mm dia, with 6.5 mm Fir Tree, PA66HIRHSUV, Black, 2000/ctn

Article Number	156-03301
Type	MOC5FMOC5FT6.5M
Color	Black (BK)
Quantity Per	carton
Product Description	The MOC with round fir tree features two of HellermannTyton's unique retention clips for dual routings, plus an integrated fir tree to fit securely in a 6.5 (+/-0.4) mm hole. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point against a panel.
Short Description	MOC Clip, 5 mm dia, 5 mm dia, with 6.5 mm Fir Tree, PA66HIRHSUV, Black, 2000/ctn
Global Part Name	MOC5FMOC5FT6.5M-PA66HIRHSUV-BK

Length L (Imperial)	1.10
Length L (Metric)	28.0
Height H (Imperial)	1.04
Height H (Metric)	26.3
Depth D (Imperial)	0.39
Depth D (Metric)	10.0
Mounting Hole Diameter D (Imperial)	0.25 " HEX; 0.26
Mounting Hole Diameter D (Metric)	6.5 mm (+/- 0.4 mm) 6.35 mm (hexagonal)
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 2000

Package Quantity (Metric) 2000

Customs Number 3926909988