

Specification Sheet

Part Number: 156-03613

Patented retention design on clip features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Fixed connector controls routing orientation.

Cable tie accommodates a wide range of secondary bundle sizes.



MOC Clip, 10 mm, Assembled to T50R Tie Rotated 90 degrees, PA66HIRHSUV, Black, 2000/ctn

Article Number

156-03613

Type

T50RMOC10SAD

Color

Black (BK) Natural (NA)

Quantity Per

carton

Product Description

The two-piece design of this assembly features an MOC with saddle paired with a T50R tie to keep two routings secured together while providing a fixed orientation for each bundle. This version enables the two routings to run perpendicular to one another. Tie provides additional security against axial slip by clamping around solid tube, pipe or harness.

Short Description

MOC Clip, 10 mm, Assembled to T50R Tie Rotated 90 degrees, PA66HIRHSUV, Black, 2000/ctn

Global Part Name T50RMOC10SAD-PA66HIRHSUV/PA66HIRHS-BK/NA

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 7.95

Length L (Metric) 202.0

Fixation Method Omega Clip

Identification Plate Position none

Bundle Diameter Min (Imperial) 0.37

Bundle Diameter Min (Metric) 9.5

Bundle Diameter Max (Imperial) 0.45

Bundle Diameter Max (Metric) 11.5

Height H (Imperial) 1.25

Height H (Metric) 31.9

Depth D (Imperial) 0.39

Depth D (Metric) 10.0

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Foot Part Material	PA66HIRHS
Material Shortcut	PA66HIRHS PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988