

## Specification Sheet

Part Number: 156-03973

Made from 100% post-industrial recycled material, this product delivers the same elevated performance as our products made from standard impact-modified, heat-stabilized material.

The ReSource family of products helps companies meet their sustainability goals.

All-in-one bundling and fastening solution reduces costs and assembly time.

Fir tree provides low insertion effort yet demonstrates high extraction resistance.



2-Piece Tie/Fir Tree Mount, Unassembled Set, 8.0"L, 0.24 - 0.26" Mounting Hole, PA66HIRHS(REC100), Blk, 2000/ctn

Article Number

156-03973

Type

T50RFT6.5SDLGSET

Color

Black (BK)

Quantity Per

carton

Product Description

Part of our sustainable line of products, the ReSource product family features solutions made from excess plastic left over from the manufacturing process or from consumers. This fir tree mount is made from 100 percent postindustrial recycled plastic. It provides a secure grip in a mounting hole. The fir tree provides a low push-in force and high pull-out resistance. The mount can slide along the cable tie to adjust orientation as needed. The mount is sold as an assembly with the cable tie.

Short Description	2-Piece Tie/Fir Tree Mount, Unassembled Set, 8.0"L, 0.24 - 0.26" Mounting Hole, PA66HIRHS(REC100), Blk, 2000/ctn
Global Part Name	T50RFT6.5SDLGSET-PA66HIRHS(REC100)-BK
Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.0
Length L (Metric)	202.0
Fixation Method	Fir tree for round holes
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.30
Width W (Metric)	7.80
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97

Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	1.11
Height H (Metric)	28.07
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.49
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	12.5
Mounting Hole Diameter D (Imperial)	0.24 - 0.26
Mounting Hole Diameter D (Metric)	6.1 - 6.7 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.7
Material	Polyamide 6.6 recycled, high impact modified, heat stabilized (PA66HIRHS(REC100))
Material Shortcut	PA66HIRHS(REC100)
Flammability	UL 94 HB

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS Compliant Yes

Package Quantity (Imperial) 2000

Package Quantity (Metric) 2000

Customs Number 3926909988