

Specification Sheet

Part Number: 156-04035



Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation.

Fir tree provides low insertion effort yet demonstrates high extraction resistance.

Disc feature prevents rattling in high-vibration applications and protects against debris ingress.

2-Piece Cable Tie/Fir Tree Mount, 6.5mm Hole and M8 Threaded Hole, PA66HIRHS/UV, BK/OG, 5000/ctn

Article Number	156-04035
Type	WSIDFTM8WSSDSET
Color	Orange (OG), High Voltage (HV) Black (BK)
Quantity Per	carton
Product Description	HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.
Short Description	2-Piece Cable Tie/Fir Tree Mount, 6.5mm Hole and M8 Threaded Hole, PA66HIRHS/UV, BK/OG, 5000/ctn

Global Part Name

WSIDFTM8WSSDSET-PA66HIRHS/PA66HIRHSUV-OG/BK

Minimum Tensile Strength (Imperial)

120

Minimum Tensile Strength (Metric)

533

Length L (Imperial)

12.1

Length L (Metric)

307.0

Fixation Method

Fir tree for round holes

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.88

Width W (Metric)

22.6

Bundle Diameter Min (Imperial)

0.37

Bundle Diameter Min (Metric)

9.4

Bundle Diameter Max (Imperial)

3.25

Bundle Diameter Max (Metric)

82.6

Height H (Imperial)	0.89
Height H (Metric)	22.77
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.23
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 - 0.28
Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm M8 Threaded
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.0
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHS PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes

UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	1200
Package Quantity (Metric)	1200

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)