

Specification Sheet

Part Number: 156-04049



Anti-rotation pin eliminates movement of bundle when fastening bolt.

Heavy duty mount with robust 120 lb tie delivers an ultra strong alternative to metal clamps.

Assembly withstands vibrations and displacement forces.

Metal bushing accommodates high tightening torque.

2-Piece Cable Tie/Screw Mount, 15" Long, M8 Hole, 4.1" Max Bundle Dia, 120lb, PA66HIRHS, Black/OG, 2500/ctn

Article Number	156-04049
Type	T120RCPCM8-TSSET
Color	Orange (OG), High Voltage (HV) Black (BK)
Quantity Per	bag
Product Description	These heavy duty cable tie mounts, secured with mechanical fasteners, include an anti-rotation pin that keeps the mount and harness assembly in position during the torquing of the bolt or nut. They provide an attachment point for securing and routing a single bundle. The mounts provide the highest level of fastening for critical cable security.
Short Description	2-Piece Cable Tie/Screw Mount, 15" Long, M8 Hole, 4.1" Max Bundle Dia, 120lb, PA66HIRHS, Black/OG, 2500/ctn

Global Part Name

T120RCPCM8-TSSET-PA66HIRHS-OG/BK

Minimum Tensile Strength (Imperial)

120

Minimum Tensile Strength (Metric)

535

Length L (Imperial)

14.96

Length L (Metric)

42.6

Fixation Method

Screw Mount

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.87

Width W (Metric)

20.0

Bundle Diameter Min (Imperial)

0.2

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

4.13

Bundle Diameter Max (Metric)

105.0

Height H (Imperial)	0.92
Height H (Metric)	23.5
Cable Tie Width Max (Imperial)	0.3
Mounting Hole Diameter D (Metric)	M8
Mounting Hole Diameter D Min (Imperial)	0.32
Mounting Hole Diameter D Max (Imperial)	0.33
Mounting Hole Diameter D Max (Metric)	8.5
Stud Diameter (Metric)	8.0 mm
Stud Diameter (Imperial)	0.31
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Foot Part Material	PA66HIRHSUV
Material Shortcut	PA66HIRHS
Material Cable Tie	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Flammability	UL 94 HB
Halogen Free	Yes

Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	2500
Package Quantity (Metric)	2500
Customs Number	3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)