

Specification Sheet

Part Number: 156-04063



Pre-assembled 2-piece fixing tie with coupler

Cable tie head can be moved after bundling

Easy addition of cables after assembly

For parallel routing of bundles that can be twisted 90° even after installation

3-Piece Wide Strap Tie with Coupler, 15"L, 0.39 - 4.13" Dia, 120lbs, HIRHS/HIRHSUV, OG/BK, 1000/ctn

Article Number 156-04063

Type T120RCOUPLER

Color Orange (OG), High Voltage (HV) Black (BK)

Quantity Per carton

Product Description
The Coupler is the simple way to connect two cable ties for a parallel routing of two bundles. This special design allows the ties 90 degrees of rotation. This is ideal for all applications where the cable, pipe or hose should move flexible in relation to the fixing point. The Coupler can be used with one or two cable ties. This allows easily subsequent installation or replacements of further cables, pipes or hose.

Short Description
3-Piece Wide Strap Tie with Coupler, 15"L, 0.39 - 4.13" Dia, 120lbs, HIRHS/HIRHSUV, OG/BK, 1000/ctn

Global Part Name

T120RCOUPLER-PA66HIRHS/PA66HIRHSUV-OG/BK

Minimum Tensile Strength (Imperial) 120

Minimum Tensile Strength (Metric) 535

Length L (Imperial) 14.96

Length L (Metric) 390.0

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.30

Width W (Metric) 7.6

Bundle Diameter Min (Imperial) 0.39

Bundle Diameter Min (Metric) 10.0

Bundle Diameter Max (Imperial) 4.13

Bundle Diameter Max (Metric) 105.0

Bundle Diameter 1st Loop Max (Imperial) 3.937

Bundle Diameter 1st Loop Max (Metric)	100.0
Bundle Diameter 2nd Loop Max (Imperial)	3.937
Bundle Diameter 2nd Loop Max (Metric)	100.0
Height H (Imperial)	0.58
Height H (Metric)	14.9
Cable Tie Width Max (Imperial)	0.3
Cable Tie Width Max (Metric)	7.62
Disc Diameter (Metric)	16.0
Disc Diameter (Imperial)	0.62
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHSUV PA66HIRHS
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)

ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988