

Specification Sheet

Part Number: 156-04238



These assemblies consist of two cable ties and a weld stud mounting base - supplied pre-assembled for ease and speed of installation.

It features a 'soft-push' design - no tools are required to fit the parts to the stud.

Ideal for installation onto the stud prior to attaching the cable, since there are no lateral tolerances required.

3-Piece M5/T5/M6/T6 Stud Mount Ties, 8" L, 50lb Tensile Strength, PA66HS/PA66HIRHS, BK, 500/pkg

Article Number 156-04238

Type T50ROX2SBS5-6U

Color Black (BK)

Quantity Per bag

Product Description Three-piece design enables up to two separate bundles to be fastened to the same stud. The preassembled part provides ease of installation. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description 3-Piece M5/T5/M6/T6 Stud Mount Ties, 8" L, 50lb Tensile Strength, PA66HS/PA66HIRHS, BK, 500/pkg

Global Part Name T50ROX2SBS5-6U-PA66HS/PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 200

Length L (Imperial) 7.95

Length L (Metric) 202.0

Fixation Method Stud Mount

Identification Plate Position none

Tie Closure plastic pawl

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.16

Bundle Diameter Min (Metric) 4.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Height H (Imperial) 0.05

Height H (Metric) 1.2

Stud Diameter (Metric)	M5 M6
Stud Diameter (Imperial)	0.20
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Foot Part Material	PA66HIRHSUV
Material Shortcut	PA66HIRHSUV PA66HS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500

Customs Number

3926909988

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)